2008 Solar Annual Review Meeting

Session: CSP Trough Systems

Company or Organization: Abengoa Solar

Funding Opportunity: CSP Trough Systems Solicitation



Hank Price Abengoa Solar Inc. Lakewood, CO 80215

ABENGOA SOLAR

Overview



- Relationship to Solar Program Goals
 - "...to make CSP cost competitive in the intermediate power markets by 2015 (~7¢/kWh with 6 hours of storage) and in baseload power markets (~5¢/kWh with 16 hours of storage) by 2020."
- Project description
- Major Activities
- FY08 Progress
- FY09 Planned Activities
- FY10 and Beyond

- Parabolic Trough Collector Development
- Reflective Film Development
- Molten-Salt Heat Transfer Fluid for Parabolic Trough Plant

Parabolic Trough Collectors

Technologies Addressed

Trough Component Manufacturing parabolic trough concentrators

Description

Development of innovative and improved parabolic trough concentrator designs that can have a major impact on this cost element.

DOE Goals Served

LCOE / U.S. based manufacturing

LCOE Impact

Potential to meet DOE 2015 cost target



| Resources (\$) | | |
|----------------|-----------|------------|
| Total Project | DOE Funds | Cost Share |
| \$624K | \$499K | \$125K |

- The goal of this project is to reduce the cost of near term parabolic trough collector technologies.
- This project will analyze the concentrator structure, the reflector that integrates into that structure, foundations and installation techniques components that comprise over 60% of the installed cost of a parabolic trough solar field.
- We will conduct a detailed evaluation of several concentrator designs, broken into three phases. Each phase has a progressively increasing scale, starting with single modules, then progressing to half-loops and on to multiple loops.

Tasks

Phase I Collector Analysis

2008

- Metrics
- Models (optical & structural)
- Design & Cost Analysis
- Prototypes
- Optical & Structural Testing

Phase II Prototype Collector Field Tests 2009

- Full-scale wind load testing
- Field Deployments
- Installation Methods
- Advanced Concentrator Design
- Economic Analysis

Phase III Collector Loop Tests

2010

Advanced Polymeric Reflectors

Technologies Addressed

Trough component manufacturing - mirrors

Description

An advanced solar reflective material will be transitioned from laboratory scale to limited production runs at commercial scale.

DOE Goals Served

LCOE / U.S. based manufacturing

LCOE Impact

\$.005/KWh



| Resources (\$) | | | |
|----------------|-----------|------------|--|
| Total Project | DOE Funds | Cost Share | |
| \$560K | \$448K | \$112K | |

- The reflective film project will develop and scale-up a previously demonstrated advanced solar reflector material (ASRM) for use in CSP applications. This technology is promising both for it's potential lower cost, and potential new low-cost concentrator designs based on it's flexibility and durability.
- An existing ASRM, last produced in 2003 under sponsorship by NREL, will be transitioned from a laboratory-scale to limited production runs on a commercial scale 48-inch wide roll coater. This objective is broken into smaller objectives to be pursued in three phases corresponding to budget periods:

ABENGOA SOLAR

| Tasks | |
|--|------|
| Phase I Transfer, model, and validate roll to roll ASRM processes | 2008 |
| Phase II Scale-up to pilot production Build Pilot Production Chamber Produce and Test Pilot Production Samples Collector Test Samples Update Cost Model | 2009 |
| Phase III Additional scale-up and field testing/validation Upgrade deposition to full width Produce and Test Limited Production Samples Collector Test Samples Test performance/durability through NREL Update Cost Model | 2010 |

Molten Salt Heat Transfer Fluid

Technologies Addressed

Advanced low cost thermal storage for CSP power plants

Description


Combine the use of a molten salt heat transfer fluid with molten salt thermal energy storage to reduce costs and increase the dispatchability of CSP plants.

DOE Goals Served

LCOE / Thermal energy storage

LCOE Impact

10-15% with storage



| Resources (\$) | | |
|----------------|-----------|------------|
| Total Project | DOE Funds | Cost Share |
| \$625k | \$500k | \$125k |

- The goal of this effort will be to develop the technologies required to allow the low freeze point molten-salts to be used in a parabolic trough solar field and to provide the opportunity to conduct the field testing necessary to allow this technology to be introduced into commercial solar plants at the end of this effort.
- Phase 1 activities focus on the initial research and development necessary to prove the feasibility of molten salt HTF in the solar field.
- Phase II includes development of prototypes and small scale testing of the technologies developed in phase I.
- Phase III is full-scale and/or field testing of various components.

Phase I Concept Feasibility

2008

- Molten-salt Design Basis
- Develop molten-salt collector technology (collector, interconnect, receiver, freeze protection)
- Molten-Salt Plant Design (SF, TES, SGS, BOS)
- Engineering Assessment

Phase II Prototype Development

2009-2010

- Test Collector Interconnection
- Test Freeze Protections
- Prototype Collector
- Laboratory Thermocline TES Test
- Test Loop Design

Phase III Field Demonstration

2010-2011

- Molten-Salt Collector Loop
- Expanded Molten-salt Collector Field
- Thermocline Test
- Operational Testing
- Final Assessment

Status

- Negociating contract with DOE
- Detailed project planning
- Staffing
- Precontract work:
 - Developing optical and structural modeling and testing capabilities
 - Abengoa Solar (Spain) working on Solucar TR design
 - Work progressing on IST designs (NREL R&D contract)
 - Developing aluminum design

EuroTrough II



IST PT-2



Solucar TR



Others:


- IST Focal Point Power Trough
- Aluminum
- Others











Phase II


- Collector Development
 - Full-scale wind testing
 - Prototyping of near-term & advanced collector designs
 - Loop testing of near-term collector designs
- Reflective Film
 - Scale-up of reflective film roll coater
- Molten-Salt
 - Testing of molten-salt components
 - Prototype molten-salt collector
 - Lab scale test of thermocline TES
- Budgets (TBD)

Phase III Activities

- Collector Development
 - Loop testing of near-term and advanced collectors
- Reflective Film
 - Scale-up to production roll to roll coater
 - Molten-salt HTF
 - Field test of collector loop (s)
 - Molten-salt thermocline TES system test

SunLab Support

- Collector
 - VSHOT Testing
 - Optical modeling support
 - Optical efficiency test
 - Full-scale wind testing
- Reflective Film
 - Optical materials technical support and characterization
- Molten-Salt
 - Low-temperature molten-salt
 - Testing TBD in Phase I
- Other
 - TOP Testing



Plant Size: 280 MW gross generation,

2 x140 MW turbines

(~250 MW net after station

parasitic loads)

Thermal Energy Storage: 6 hours of generation

Collector Type: Parabolic Trough

Collector Area: 2,200,000 m²

Land Area: 3 square miles

Annual Generation: 900,000,000 kWh

41% annual capacity factor

On-Peak Generation:
 95% capacity factor

hours noon - 8 pm

June – September

Expected On-Line Date: 2011

Solana Generating Station



- Parabolic mirrors heat a petroleumbased fluid.
- 2 Hot fluid returns from the solar field.
- The hot fluid transfers its heat energy to water, creating steam.
- 4 Steam drives a turbine, producing electricity.
- **5** The hot fluid will also heat molten salt.
- 6 If the sun is not shining, the fluid can be heated by the molten salt.
- Fluid sent back to the solar fields.

- "Solana" Spanish for "sunny place."
- Plant located on agricultural land 70 miles southwest of Phoenix, near Gila Bend, Ariz.
- Will generate enough electricity to serve 70,000 APS customers
- Over \$1 billion in total investment
- 1,500 construction jobs over 2 years
- 85 full time jobs to operate and maintain the plant



- Will use 1/4 the amount of water of current crop usage.
- Will generate 50x as much revenue per acre as crops
- APS Considers Project Economically Attractive but requires the 30% ITC extension.